

वस्त्रादि — कपास करघों के लिए निचला
शाफ्ट — विशिष्टि

(दूसरा पुनरीक्षण)

**Textiles — Bottom Shaft for Cotton
Looms — Specification**

(Second Revision)

ICS 59.120.30

© BIS 2023



भारतीय मानक ब्यूरो
BUREAU OF INDIAN STANDARDS
मानक भवन, 9 बहादुर शाह ज़फर मार्ग, नई दिल्ली - 110002
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI - 110002
www.bis.gov.in www.standardsbis.in

FOREWORD

This Indian Standard (Second Revision) was adopted by the Bureau of Indian Standards, after the draft finalized by the Textile Machinery and Accessories Sectional Committee had been approved by the Textiles Division Council.

Picking motion is originated from the bottom shaft. Two picking cams are mounted on the bottom shaft, one on each side therefore one revolution of bottom shaft ensures the insertion of two picks. Timing of picking is changed by turning the cam on the bottom shaft.

This standard was originally published in 1963 and subsequently revised in 1978. This revision has been made in the light of experience gained since its publication and to incorporate the following major changes:

- a) Title of the standard has been modified;
- b) Marking, packing and sampling clauses have been modified; and
- c) References to Indian standards have been updated.

The composition of the Committee responsible for the formulation of this standard is listed in Annex D.

For the purpose of deciding whether a particular requirement of this standard is complied with the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS 2 : 2022 ‘Rules for rounding off numerical values (*second revision*)’. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

*Indian Standard***TEXTILES — BOTTOM SHAFT FOR COTTON LOOMS — SPECIFICATION***(Second Revision)***1 SCOPE**

This standard prescribes the requirements for bottom shaft for plain and automatic cotton looms.

2 REFERENCES

The standards listed in Annex A contain provisions which, through reference in this text, constitute provisions of this standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent editions of these standards.

3 TERMINOLOGY

For the purpose of this standard reed space (of the loom) shall mean maximum space available on the loom for the insertion of a reed, that is, the overall width of a reed which can be fixed on the loom.

4 MANUFACTURE**4.1 Material**

Bottom shaft shall be manufactured from bright bar conforming to IS 7283.

4.2 Workmanship and Finish

The shaft shall be straight and free from rust. The diameter of the shaft should be uniform throughout without any hammer marks. Both ends of the shaft shall be chamfered.

4.3 Shape

The shaft shall generally be as shown in Fig. 1.

NOTE — Extra machining, such as keyways and step diameters shall be done according to special design requirements.

5 REQUIREMENTS**5.1 Dimensions**

The length of bottom shaft shall be within coarse class deviations for linear dimensions specified in IS 2102 (Part 1) and reproduced in Annex B for ready reference. The diameter of the shaft shall have a fit of H8 according to IS 919 (Part 1).

5.2 True Running

The bottom shaft shall run true. However, when tested by the method given in Annex C the out of true running, if present, shall not exceed 0.025 mm.

5.3 Screw Threads

Bottom shaft shall preferably be provided with screw threads conforming to IS 4218 (Part 4) and at one of its ends over a length of 50 mm (see Fig. 1).

6 MARKING**6.1** Each component shall be marked with the following information:

- Manufacturer's name, initials or trade-mark, if any;
- Reed space of the loom on which the bottom shafts are to be used;
- Number of bottom shafts;
- Diameter of bottom shafts;
- Gross and net mass;
- Lot/batch number;
- Country of origin; and
- Any other information required by the law in force and/or by the buyer.




FIG. 1 BOTTOM SHAFT

6.2 BIS Certification Marking

The product(s) conforming to the requirements of this standard may be certified as per the conformity assessment schemes under the provisions of the *Bureau of Indian Standards Act, 2016* and the Rules and Regulations framed thereunder, and the products may be marked with the Standard Mark.

7 PACKING

The bottom shafts shall be coated lightly with anti-

rust agent and shall be packed in a wooden case provided with supports so that they do not touch each other. The wooden case shall be strong enough to withstand the hazards of transit.

8 SAMPLING

Unless otherwise agreed to between the buyer and the seller, to ascertain the conformity of bottom shaft to the requirements of this specification, or as specified in IS 2500 (Part 1) shall be followed.

ANNEX A

(Clause 2)

LIST OF REFERRED STANDARDS

IS No.	Title	IS No.	Title
IS 919 (Part 1) : 2014	Geometrical product specifications (GPS) — ISO code system for tolerances on linear sizes: Part 1 Basis of tolerance, deviation and fits (<i>third revision</i>)		indexed by acceptance quality limit (AQL) for lot by lot inspection (<i>third revision</i>)
IS 2102 (Part 1) : 1993	General tolerances: Part 1 Tolerances for linear and angular dimensions without individual tolerance indications (<i>third revision</i>)	IS 4218 (Part 4) : 2001	ISO general purpose metric screw threads: Part 4 Selected sizes for screws, bolts and nuts (<i>second revision</i>)
IS 2500 (Part 1) : 2000	Sampling procedures for inspection by attributes: Part 1 Sampling schemes	IS 7283 : 1992	Hot-Rolled bars for the production of bright bars and machined parts for engineering applications specification (<i>first revision</i>)

ANNEX B

(Clause 5.1)

LENGTH OF BOTTOM SHAFT

Extract from IS 2102 (Part 1)

Sl No.	Range of Nominal Dimensions (mm)	Tolerance (mm)	
(1)	(2)	(3)	
i)	Greater than 3 and less than equal to 6	± 0.2	
ii)	Greater than 6 and less than equal to 30	± 0.5	
iii)	Greater than 30 and less than equal to 120	± 0.8	
iv)	Greater than 120 and less than equal to 315	± 1.2	
v)	Greater than 315 and less than equal to 1 000	± 2	
vi)	Greater than 1 000 and less than equal to 2 000	± 3	
vii)	Greater than 2 000 and less than equal to 4 000	± 4	
viii)	Greater than 4 000 and less than equal to 8 000	± 5	

ANNEX C

*(Clause 5.2)***METHOD FOR CHECKING TRUE RUNNING**

C-1 A surface plate, two 'V' blocks and a micrometer dial gauge shall be used for the purpose of this test.

C-2 Set the 'V' blocks on the surface plate. Take a bottom shaft and mount it in the 'V' blocks. Set the micrometer dial gauge in such a way that its anvil head is held in contact with the surface of the bottom shaft. Adjust its pointer at zero position. Rotate the shaft once. Observe the maximum deflection of the

pointer of the micrometer dial gauge on both sides of the zero position. Add the two maximum values and divide the sum by two.

C-3 Repeat the test at 4 more places along the length of the bottom shaft.

C-4 Report the bottom shaft to be in conformity with the requirements of **5.2**.

ANNEX D
(Foreword)

COMMITTEE COMPOSITION

Textile Machinery and Accessories Sectional Committee, TXD 14

<i>Organization</i>	<i>Representative(s)</i>
Central Manufacturing Technology Institute, Bengaluru	DR NAGAHANUMAIAN (Chairperson)
ATE Enterprises Private Limited, New Delhi	SHRI ABHIJIT KULKARNI SHRI ANIL KUMAR SHARMA (<i>Alternate</i>)
Amritlakshmi Machine Works, Mumbai	SHRI N. K. BRAHMACHARI SHRI N. K. RAUT (<i>Alternate</i>)
Bhowmick Calculator, Kolkata	SHRI GOUTAM BHOWMICK SHRI VIVEKANANDA BHOWMICK (<i>Alternate</i>)
Central Manufacturing Technology Institute, Bengaluru	SHRI B. R. MOHANRAJ SHRI K. SARAVANAN (<i>Alternate</i>)
Confederation of Indian Textile Industry, New Delhi	SHRI AJAY KUMAR
Dashmesh Jacquard and Powerloom Private Limited, Panipat	SHRI RAJMEET DHAMMU (<i>Representative</i>)
HLL Lifecare Limited, Noida	SHRI AKHIL G. S. SHRI RATNAKAR GUPTA (<i>Alternate</i>)
ICAR-Central Institute for Research on Cotton Technology, Mumbai	DR V. G. ARUDE DR T. SENTHILKUMAR (<i>Alternate</i>)
India ITME Society, Mumbai	SHRI PRASHANT MANGUKIA SHRIMATI SEEMA SRIVASTAVA (<i>Alternate</i>)
Indian Jute Industries Research Association, Kolkata	SHRIMATI SAUMITA CHOUDHURY SHRI PARTHA SANYAL (<i>Alternate</i>)
Indian Textile Accessories and Machinery Manufacturers Association, Mumbai	SHRI N. D. MHATRE SHRI CHANDRESH SHAH (<i>Alternate</i>)
Inspiron Engineering Private Limited, Ahmedabad	SHRI SANJAY KOWARKAR SHRI PRATYUSH B. CHAUHAN (<i>Alternate</i>)
JCB Industries, Guwahati	SHRI DHRUBA SARMA SHRI ABHIJIT BHUYAN (<i>Alternate</i>)
Kusters Calico Machinery Limited, Karjan	SHRI DEVANG PARikh SHRI SHUBHASIS SUR (<i>Alternate</i>)
Lakshmi Machine Works Limited, Coimbatore	SHRI V. LAKSHMI VARADHARAJAN
Laxmi Shuttleless Looms Private Limited, Ahmedabad	SHRI KETAN SANGHVI
Man Made Textiles Research Institute, Surat	DR S. K. BASU
Ministry of Heavy Industries and Public Enterprises, Department of Heavy Industry, New Delhi	SHRI SNAJEEV GUPTA SHRI S. SUNDAR (<i>Alternate</i>)
National Safety Council, Navi Mumbai	SHRI LALIT R. GABHANE SHRI R. R. DEOGHARE (<i>Alternate</i>)
Office of the Textile Commissioner, Mumbai	SHRI C. R. KALESAN SHRI JAGRAM MEENA (<i>Alternate</i>)
Peass Industrial Engineers Private Limited, Navsari	SHRI RAVI S. RAO SHRI JIGNESH B. PATEL (<i>Alternate</i>)

<i>Organization</i>	<i>Representative(s)</i>
Technocraft Industries India Limited, Mumbai	SHRI RAVINDER KUMAR SHRI DURADUNDESHWAR HIREMATH (<i>Alternate</i>)
Textile Machinery Manufacturers Association, Mumbai	SHRI M. SHANKAR SHRI PRASHANT MANGUKIA (<i>Alternate</i>)
The Bombay Textile Research Association, Mumbai	SHRI VIJAY GAWDE SHRI R. A. SHAIKH (<i>Alternate</i>)
The Synthetic and Art Silk Mills Research Association, Mumbai	DR MANISHA MATHUR SHRI SANJAYA SAINI (<i>Alternate</i>)
The Textile Association (India), Mumbai	SHRI J. B. SOMA SHRI ASHOK JUNEJA (<i>Alternate</i>)
Truetzschler India Private Limited, Ahmedabad	SHRI PRAVIN KANDGE SHRI SHILADITYA JOSHI (<i>Alternate</i>)
United Nations International Children's Emergency Fund, New Delhi	DR PRATIBHA SINGH SHRI YUSUF KABIR (<i>Alternate</i>)
Veermata Jijabai Technological Institute, Mumbai	DR SURANJANA GANGOPADHYAY SHRI S. P. BORKAR (<i>Alternate</i>)
BIS Directorate General	SHRI J. K. GUPTA, SCIENTIST 'E'/DIRECTOR AND HEAD (TEXTILES) [REPRESENTING DIRECTOR GENERAL (<i>Ex-officio</i>)]

Member Secretary
SHRI SWAPNIL
SCIENTIST 'B'/ASSISTANT DIRECTOR
(TEXTILES), BIS

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act, 2016* to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Head (Publication & Sales), BIS.

Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the website- www.bis.gov.in or www.standardsbis.in.

This Indian Standard has been developed from Doc No.: TXD 14 (20008).

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002
Telephones: 2323 0131, 2323 3375, 2323 9402

Website: www.bis.gov.in

Regional Offices:

Central	: 601/A, Konnectus Tower -1, 6 th Floor, DMRC Building, Bhavbhuti Marg, New Delhi 110002	{ 2323 7617
Eastern	: 8 th Floor, Plot No 7/7 & 7/8, CP Block, Sector V, Salt Lake, Kolkata, West Bengal 700091	{ 2367 0012 2320 9474
Northern	: Plot No. 4-A, Sector 27-B, Madhya Marg, Chandigarh 160019	{ 265 9930
Southern	: C.I.T. Campus, IV Cross Road, Taramani, Chennai 600113	{ 2254 1442 2254 1216
Western	: Plot No. E-9, Road No.-8, MIDC, Andheri (East), Mumbai 400093	{ 2821 8093

Branches : AHMEDABAD. BENGALURU. BHOPAL. BHUBANESHWAR. CHANDIGARH. CHENNAI.
COIMBATORE. DEHRADUN. DELHI. FARIDABAD. GHAZIABAD. GUWAHATI.
HIMACHAL PRADESH. HUBLI. HYDERABAD. JAIPUR. JAMMU & KASHMIR.
JAMSHEDPUR. KOCHI. KOLKATA. LUCKNOW. MADURAI. MUMBAI. NAGPUR.
NOIDA. PANIPAT. PATNA. PUNE. RAIPUR. RAJKOT. SURAT. VISAKHAPATNAM.